



**DECTRIS**  
detecting the future



# MYTHEN2 R

*HPC microstrip X-ray detectors for laboratory applications*



Getting the perfect detector for X-ray diffraction, scattering or spectroscopy experiments does not require a compromise. The widest portfolio of MYTHEN2 microstrip detectors lets you optimize both data coverage and signal-to-noise ratio for a range of X-ray energies. Two module sizes and four sensor geometries ensure that your data is collected with the best possible detector for your application.

All MYTHEN2 detectors feature no-noise performance, high dynamic range and exceeding count rates. They advance any experiment carried out with weak or bright sources, and long or short exposure times. MYTHEN2 allows you to reach the maximal resolution of your data: its strip is the narrowest available on the market.

Easy use of the systems is achieved thanks to the versatile software interface, 3 year warranty, and maintenance-free operation.

### Key advantages

- No readout noise or dark current
- Premium resolution owing to 50  $\mu\text{m}$  strip
- Energy range from Ti to Ag
- Fluorescence suppression
- Count rate  $10^6$  counts/s per strip

### Applications

- PXRD analysis
- PDF analysis
- SAXS, WAXS, GISAXS
- Residual stress analysis
- X-ray reflectometry
- WD-XRF, EXAFS, XANES

### Scan-free data collection

MYTHEN2 modules come with 1280 (1K) or 640 (1D) strips. Depending on the geometry of the instrument, a 1K module can either collect  $25^\circ$   $2\theta$  of diffraction data or a 1.24 eV wide energy spectrum [3]. For an even wider coverage, up to four modules can be simultaneously operated using a single Detector Control System (DCS4).


### Premium resolution with 50 $\mu\text{m}$ strip

MYTHEN2 provides unprecedented resolution thanks to the narrowest strip currently available on the X-ray market. Diffractometers equipped with the MYTHEN2 detector achieve a resolution of  $0.03^\circ$   $2\theta$  (FWHM) [1] while the resolution of WD-XRF-spectrometers can reach 2 eV [2].

[1] [https://www.stoe.com/wp-content/uploads/2014/03/STOE\\_STADI\\_P-1.pdf](https://www.stoe.com/wp-content/uploads/2014/03/STOE_STADI_P-1.pdf)

[2] Németh, Z. *et al.* (2016) *Rev. Sci. Instrum.* **87**, 103105.

[3] Sato, K. *et al.* (2017) *X-Ray Spectrom.* **46**, 330-335.



## Energy range from 4 to 40 keV

The wide MYTHEN2 portfolio comprises four sensor geometries, each optimized to deliver the optimal efficiency and signal-to-noise ratio for a chosen energy range. The combination of 320  $\mu\text{m}$  sensor thickness and 4 mm strip length allows detection of energies as low as 4 keV. The 1000  $\mu\text{m}$  sensor provides high efficiency even for Mo or Ag radiation.

## OEM partners

MYTHEN2 detectors are integrated in diffractometers and stress robots of the following producers:

- Anton Paar
- Bourevestnik
- GNR
- MRX
- Proto
- Shimadzu
- STOE
- Stresstech
- Xplorex
- XRD Eigenmann


## Technical specifications

MYTHEN2 R	1K	1D
<b>Sensor thickness [<math>\mu\text{m}</math>]</b>	320, 450, 1000	320, 450
<b>Strip width [<math>\mu\text{m}</math>]</b>	50	
<b>Strip length [mm]</b>	8	8 (450 $\mu\text{m}$ ) 4 (320 $\mu\text{m}$ )
<b>Dynamic range [bit]</b>	24	
<b>Energy range [keV]</b>	4-40*	
<b>Readout time [<math>\mu\text{s}</math>]</b>	89	
<b>Frame rate [Hz]</b>	25	
<b>Point-spread function [strip]</b>	1	
<b>Energy resolution (rms) [eV]</b>	687	
<b>Cooling</b>	Air	
<b>Module dimensions (WHD) [<math>\text{mm}^3</math>]</b>	70x62x22	38x62x22
<b>Module weight [g]</b>	180	100
<b>DCS4 dimension (WHD) [<math>\text{mm}^3</math>]</b>	110x30x160	
<b>DCS4 weight [g]</b>	400	

\* X-ray energies down to 4 keV are available only with the 320  $\mu\text{m}$  x 4 mm sensors.

All specifications are subject to change without notice.





**DECTRIS Ltd.**  
Täferweg 1  
5405 Baden-Dättwil  
Switzerland

Phone +41 56 500 21 00  
Fax +41 56 500 21 01  
E-Mail [sales@dectris.com](mailto:sales@dectris.com)  
[www.dectris.com](http://www.dectris.com)

Registered trademarks: „DECTRIS“: EU, JP, CN, KR (IR0911969), USA (5,253,168)  
“detecting the future“: EU, CN, KR, JP, AUS (1191333), USA (4,607,800)  
“DECTRIS Instant Retrigger“: EU, CN, KR, JP, AUS (1224728), USA (4,797,363)  
„DECTRIS MYTHEN“: JP, KR, CH, EU, AUS (IR1350261), USA (5,499,834)  
© 2018 DECTRIS Ltd., all rights reserved • Subject to technical modifications;  
Rev.0. • Printed 05/2019